


REV	MODIFICATIONS	DRAWN BY	CHECKED BY	DATE
A	CREATION	GI	GI	1/23/2011



Colour	HF Marine Band
HF Marine Band	Standard is Black. Optional White.
Length	3.65 metres (12 ft)
Pattern	Omnidirectional
Polarisation	Vertical
Base Diameter	17mm (0.625 in)
Frequency Range	Pre-tuned to frequency, or unloaded 2-30 MHz with suitable ATU
Wind Loading	2.54 kg at 100 km/h (5.6 lbs at 60 mph) 4.3 kg at 130 km/h (9.5 lbs at 81 mph)
Power Capability	400W PEP for unloaded top sections, 250W PEP for normal loaded top sections; higher power to order
Mountings	Two 50mm (2 in) nylon clamp type insulators, 30mm (1 3/16 in) diameter, threaded to take ¼ inch UNC Whitworth bolt (not supplied); insulator spacing not less than 38cm (1.25 ft)
Connection	Silicone insulated flexible cable tail 2m long (6.5 ft) 56/0.3 tinned copper; length should not exceed that provided for correct operation on the higher frequencies
Packed Weight	2 kg (4.4 lbs) with mountings

UNLESS OTHERWISE SPECIFIED DIMENSIONS : mm ANGLES : d.		NEARSON INC.			
CUSTOMER N°	TITLE :	Marine antenna for smaller marine vessels			
FILE N°					
		SIZE A4	NMO-01-0012		
		SCALE : N.D.		<table border="1"> <tr> <td>REV A</td> <td>Doc.</td> </tr> <tr> <td>Prod.</td> <td></td> </tr> </table>	REV A
REV A	Doc.				
Prod.					
			SHEET 1 of 1		