

M16878E 軍規鐵氟龍隔離電纜

以軍規 MIL-W-16878/4 TYPE E 即 600V 200°C 銅鍍銀導體所組成之電纜，主要分為四大類產品，如：表一、表二、表三、表四

MIL-W-16878 鐵氟龍隔離電纜

特性：(1) 電壓 600V。

(2) 溫度 -90°C ~ 200°C。

(3) 耐酸、鹼、抗油、抗焰、抗潮、抗化學藥品及抗菌。

MIL-W-16878 鐵氟龍隔離電纜

特性：(1) 電壓 600V。

(2) 溫度 -90°C ~ 200°C。

(3) 耐酸、鹼、抗油、抗焰、抗潮、抗化學藥品及抗菌。

表一 鐵氟龍含環繞隔離無外被覆電纜




NEC Part No	NO. Of Cond.	Conductor		Nom O.D. at Max. Width
		AWG	Stranding	
NEC-T2401	1	24	19/36	.069
NEC-T2402	2	24	19/36	.112
NEC-T2403	3	24	19/36	.120
NEC-T2404	4	24	19/36	.132
NEC-T2201	1	22	19/34	.075
NEC-T2202	2	22	19/34	.124
NEC-T2203	3	22	19/34	.132
NEC-T2204	4	22	19/34	.146
NEC-T2001	1	20	19/32	.083
NEC-T2002	2	20	19/32	.142
NEC-T2003	3	20	19/32	.153
NEC-T2004	4	20	19/32	.168
NEC-T1801	1	18	19/30	.093
NEC-T1802	2	18	19/30	.162
NEC-T1803	3	18	19/30	.172
NEC-T1804	4	18	19/30	.192
NEC-T1601	1	16	19/29	.103
NEC-T1602	2	16	19/29	.184
NEC-T1603	3	16	19/29	.200
NEC-T1603	4	16	19/29	.230



佳昭企業有限公司
NEARSON ENTERPRISE CORP.

• TEL:886-2-2957-9823 • FAX:886-2-2957-9712
• <http://www.nearson.com.tw>

表二 鐵氟龍含環繞隔離加 FEP 擠出型外被覆電纜



NEC Part No	NO. Of Cond.	Conductor		Nom O.D. at Max. Width
		AWG	Stranding	
NEC-J2401	1	24	19/36	.085
NEC-J2402	2	24	19/36	.130
NEC-J2403	3	24	19/36	.135
NEC-J2201	1	22	19/34	.091
NEC-J2202	2	22	19/34	.150
NEC-J2203	3	22	19/34	.158
NEC-J2001	1	20	19/32	.100
NEC-J2002	2	20	19/32	.168
NEC-J2003	3	20	19/32	.178
NEC-J1801	1	18	19/30	.110
NEC-J1802	2	18	19/30	.188
NEC-J1803	3	18	19/30	.207
NEC-J1601	1	16	19/29	.123
NEC-J1602	2	16	19/29	.220
NEC-J1603	3	16	19/29	.235

表三 TEFLON®TAPE WRAP OVERALL



NEC Part No	NO. Of Cond.	Conductor		Nom O.D. at Max. Width
		AWG	Stranding	
NEC-W2401	1	24	19/36	.95
NEC-W2402	2	24	19/36	.140
NEC-W2403	3	24	19/36	.147
NEC-W2404	4	24	19/36	.159
NEC-W2201	1	22	19/34	.102
NEC-W2202	2	22	19/34	.154
NEC-W2203	3	22	19/34	.162
NEC-W2204	4	22	19/34	.176
NEC-W2001	1	20	19/32	.110
NEC-W2002	2	20	19/32	.170
NEC-W2003	3	20	19/32	.175
NEC-W2004	4	20	19/32	.213
NEC-W1801	1	18	19/30	.120
NEC-W1802	2	18	19/30	.190
NEC-W1803	3	18	19/30	.219
NEC-W1804	4	18	19/30	.237
NEC-W1601	1	16	19/29	.130




佳昭企業有限公司
NEARSON ENTERPRISE CORP.

• TEL:886-2-2957-9823 • FAX:886-2-2957-9712
• <http://www.nearson.com.tw>

NEC-W1602	2	16	19/29	.230
NEC-W1603	3	16	19/29	.240
NEC-W1603	4	16	19/29	.270

表四 TEFLON®IMPREGNATED BRAID OVERALL



NEC Part No	NO. Of Cond.	Conductor		Nom O.D. at Max. Width
		AWG	Stranding	
NEC-B2401	1	24	19/36	.081
NEC-B2402	2	24	19/36	.126
NEC-B2403	3	24	19/36	.133
NEC-B2404	4	24	19/36	.144
NEC-B2201	1	22	19/34	.088
NEC-B2202	2	22	19/34	.137
NEC-B2203	3	22	19/34	.144
NEC-B2204	4	22	19/34	.158
NEC-B2001	1	20	19/32	.097
NEC-B2002	2	20	19/32	.154
NEC-B2003	3	20	19/32	.163
NEC-B2004	4	20	19/32	.180
NEC-B1801	1	18	19/30	.106
NEC-B1802	2	18	19/30	.174
NEC-B1803	3	18	19/30	.185
NEC-B1804	4	18	19/30	.205
NEC-B1601	1	16	19/29	.117
NEC-B1602	2	16	19/29	.196
NEC-B1603	3	16	19/29	.225
NEC-B1603	4	16	19/29	.255



佳昭企業有限公司
NEARSON ENTERPRISE CORP.

• TEL:886-2-2957-9823 • FAX:886-2-2957-9712
• <http://www.nearson.com.tw>