

MIL-C-7078 空用軍規 PVC/NYLON 隔離電纜

主要由軍規 MIL-W-5086 導線組成之電纜，均有隔離，均為 600V 電壓，均為 105°C 耐溫等級，其它還有 MIL-W-81381 導線耐溫為 200°C，MIL-W-22759 導線則有耐溫 200°C 和 260°C。

MIL-C-7078C 軍規型號之表示方式

M7078/X — YY — Z

(1) (2) (3)

(1) M7078/X：選用、種類，如表一。(2) YY：單獨導線之大小。(3) Z：使用導線之數量。

表一：

型號	說明	電壓	溫度
M7078/2	Basic wires are to M5086/1, TPC Shield	600 Volt	105°C
M7078/3	Basic wires are to M5086/1, TPC Shield, Nylon Jacket	600 Volt	105°C
M7078/4	Basic wires to M5086/2, TPC Shield	600 Volt	105°C
M7078/5	Basic wires to M5086/2, TPC Shield, Nylon Jacket	600 Volt	105°C
M7078/6	Basic wires to M5086/3, TPC Shield	600 Volt	105°C
M7078/7	Basic wires to M5086/3, TPC Shield, Nylon Jacket	600 Volt	105°C
M7078/8	Basic wires to M81381/11, TPC Shield, Polyimide Tape Jacket	600 Volt	150°C
M7078/9	Basic wires to M81381/12, TPC Shield, Polyimide Tape Jacket	600 Volt	150°C
M7078/10	Basic wires to M81381/13, TPC Shield, Polyimide Tape Jacket	600 Volt	150°C
M7078/11	Basic wire to M81381/11, NPC Shield, Polyimide Tape Jacket	600 Volt	200°C
M7078/12	Basic wires to M81381/12, NPC Shield, Polyimide Tape Jacket	600 Volt	200°C
M7078/13	Basic wires to M81381/13, NPC Shield, Polyimide Tape Jacket	600 Volt	200°C
M7078/14	Basic wires to M81381/14, TPC Shield, Polyimide Tape Jacket	600 Volt	200°C
M7078/15	Basic wires to M81381/11, Unshielded and Unjacketed	600 Volt	200°C
M7078/16	Basic wires to M81381/12, Unshielded and Unjacketed	600 Volt	200°C
M7078/17	Basic wires to M81381/13, Unshielded and Unjacketed	600 Volt	200°C
M7078/18	Basic wires to M81381/14, Unshielded and Unjacketed	600 Volt	200°C
M7078/23	Basic wire to M5086/1, Unshielded and Unjacketed	600 Volt	105°C
M7078/24	Basic wire to M5086/2, Unshielded and Unjacketed	600 Volt	105°C
M7078/25	Basic wire to M5086/3, Unshielded and Unjacketed	600 Volt	105°C
M7078/26	Basic wire to M81381/8, NPC Shield, Polyimide Tape Jacket	600 Volt	200°C
M7078/27	Basic wire to M81381/8, Unshielded and Unjacketed	600 Volt	200°C
M7078/28	Basic wire to M81381/10, NPC Shield, Polyimide Tape Jacket	600 Volt	200°C
M7078/29	Basic wire to M81381/10, Unshielded and Unjacketed	600 Volt	200°C
M7078/30	Basic wire to M22759/12, 1-7 Cord, FEP Jacket	600 Volt	200°C
M7078/31	Basic wire to M22759/12, 2-7 Cord	600 Volt	260°C
M7078/32	Basic wire to M22759/23, 1-7 Cond, FEP Jacket	600 Volt	200°C
M7078/33	Basic wire to M22759/23, 2-7 Cond	600 Volt	260°C
M7078/34	Basic wire to M22759/12, 1-7 Cond, PTFE	600 Volt	260°C
M7078/35	Basic wire to M22759/23, 1-7 Cond, PTFE	600 Volt	260°C



佳昭企業有限公司
NEARSON ENTERPRISE CORP.

• TEL:886-2-2957-9823 • FAX:886-2-2957-9712
• <http://www.nearson.com.tw>