



REV	MODIFICATIONS	DRAWN BY	CHECKED BY	DATE
A	CREATION	HE	HE	1/23/2011



Colour	Standard is Black. Optional White.
HF Marine Band	2-30 MHz
Length	5.5 metres (18 ft)
Pattern	Omnidirectional
Polarisation	Vertical
Base Diameter	25.4cm (1 in) (radiator)
Frequency Range	Pre-tuned to frequency or frequencies required, or unloaded 2-30 MHz with suitable ATU
Wind Loading	4.9 kg at 100 km/h (10.8 lbs at 60 mph) 8.3 kg at 130 km/h (18.3 lbs at 81 mph)
Power Capability	800W PEP for unloaded top sections, 600W PEP for normal loaded top sections; 400W PEP for trapped top sections; higher power to order
Mounting	One integral base insulator and 12.7cm (5 in) chrome bronze flange with 'O' ring seal between insulator and flange, and 4 x 6.75mm (17/64 in) mounting holes (bolts not supplied). Centre feed through hole 15.8mm (5/8 in) dia.
Connection	Under deck to lug on feedthrough bolt
Packed Weight	5 kg (11 lbs) with mounting

UNLESS OTHERWISE SPECIFIED DIMENSIONS : mm ANGLES : d.			
CUSTOMER N°	FILE N°	TITLE : Marine antenna for vessels	
		SIZE A4	NMO-01-0016
SCALE : N.D.			
		REV A	Prod. Doc.
		SHEET 1 of 1	