



REV	MODIFICATIONS	DRAWN BY	CHECKED BY	DATE
A	CREATION	HE	HE	7/13/2011



Colour	Standard is Black. Optional White.
HF Marine Band	2-30 MHz
Length	8.8 metres (29 ft)
Pattern	Omnidirectional
Polarisation	Vertical
Base Diameter	32mm (1.25 in)
Frequency Range	Retuned to frequency or frequencies required, or unloaded 2-30 MHz with suitable ATU
Wind Loading	10.4 kg at 100 km/h (22.9 lbs at 60 mph) 17.6 kg at 130 km/h (38.7 lbs at 81 mph)
Power Capability	1 kW PEP for normal loaded or unloaded top sections; 500W PEP for trapped top sections; higher power to order
Mounting	Two 100mm (4 in) nylon clamp type insulators, 50mm (2 in) diameter, threaded to take ½ inch Whitworth bolt (not supplied); insulator spacing not less than 1.4 m (4.5 ft)
Connection	Silicone insulated flexible cable tail 2.5 m long (8 ft) 56/0.3 tinned copper; length should not exceed that provided for correct operation on the higher frequencies
Packed Weight	8 kg (17.6 lbs) with mountings

UNLESS OTHERWISE SPECIFIED DIMENSIONS : mm ANGLES : d.			
CUSTOMER N°	FILE N°	TITLE : Marine HF Antenna for large vessels	
		SIZE A4	NMO-01-0024
SCALE : N.D.			
		REV A	Prod. Doc.
		SHEET 1 of 1	